

APPLICATIONS

- ◆ Branch panel
- ◆ Main service entrance

STANDARD FEATURES

- ◆ UL & C-UL listed, CE
- ◆ 2-year warranty
- ◆ 3-line fusing with blown fuse indication
- ◆ Discharge resistors per NEC requirements
- ◆ Assembled in the USA

STANDARD RATINGS

- ◆ 240, 480, 600 V
- ◆ 3-phase
- ◆ 60 Hz

CAPACITOR CELLS

- ◆ Continuous voltage rating:
 - 528 V for 480 V application
 - 660 V for 600 V application
 - 264 V for 240 V application
- ◆ Continuous current rating: 165% of nominal
- ◆ Ambient temperature rating: 140° F
- ◆ 130,000 hours rated life
- ◆ 2-year warranty
- ◆ Self-contained, 3-phase, delta-connected
- ◆ Industrial grade dry-type construction
- ◆ Losses of less than ½ watt per kVAR
- ◆ Self-healing metallized polypropylene dielectric film
- ◆ 3-phase overpressure disconnect
- ◆ Hermetically-sealed aluminum case
- ◆ Finger-safe, maintenance free terminals

FUSES

- ◆ Fast-acting, current-limiting, with 200,000 ampere interrupting capacity

ENCLOSURES



- ◆ Built to NEMA 12 specifications for indoor use
- ◆ Wall-mounted or free-standing with hinged door and lockable door handle

FIELD WIRING TERMINATION

- ◆ Mechanical connections are provided for all field wiring termination points
- ◆ Refer to product manual for incoming conductor information

LOSS-OF-CAPACITANCE INDICATION

- ◆ Patented CelTel® brand monitoring system
- ◆ Indicates when capacitor assembly is no longer functioning effectively
- ◆ Phase imbalance indication
- ◆ Overcurrent and undercurrent indication
- ◆ Reset function
- ◆ Self diagnostic function



OPTIONS

- ◆ Circuit breaker or disconnect switch
- ◆ Other enclosure ratings available
- ◆ Other voltages and frequencies available
- ◆ Installation and start-up service