

## CNX33200-3

- ◆ 200 kVAr, 240 V, 60 Hz, 3-phase
- ◆ 481 amps

## APPLICATIONS

- ◆ Branch panel
- ◆ Main service entrance

## STANDARD FEATURES

- ◆ UL & C-UL listed, CE
- ◆ 2-year warranty
- ◆ 3-line fusing with blown fuse indication
- ◆ Discharge resistors per NEC requirements
- ◆ Assembled in the USA

## CAPACITOR CELLS


- ◆ 264 Continuous voltage rating:
- ◆ Continuous current rating: 165% of nominal
- ◆ Ambient temperature rating: 140° F
- ◆ 130,000 hours rated life
- ◆ 2-year warranty
- ◆ Self-contained, 3-phase, delta-connected
- ◆ Industrial grade dry-type construction
- ◆ Losses of less than ½ watt per kVAr
- ◆ Self-healing metallized polypropylene dielectric film
- ◆ 3-phase overpressure disconnecter
- ◆ Hermetically-sealed aluminum case
- ◆ Finger-safe, maintenance free terminals

## FUSES

- ◆ Fast-acting, current-limiting, with 200,000 ampere interrupting capacity

## FIELD WIRING TERMINATION

- ◆ Mechanical connections are provided for all field wiring termination points
- ◆ Refer to product manual for incoming conductor information



## ENCLOSURE

- ◆ Dimensions: 72 in H x 48 in W x 16 in D
- ◆ Weight: 240 lb
- ◆ Built to NEMA 12 specifications for indoor use
- ◆ Free-standing with hinged double doors, lockable door handle and removable eye bolts

## OPTIONS

- ◆ Circuit breaker or disconnect switch
- ◆ Other enclosure ratings available
- ◆ Other voltages and frequencies available