

TFPM43001-3

- ♦ Series: Siemens Industry, Inc.
- ♦ 1 kVAr, 480 V, 60 Hz, 3-phase
- ♦ 1.2 amps

APPLICATION

- ♦ At the load within Motor Control Centers (MCCs)

STANDARD FEATURES

- ♦ UL recognized component
- ♦ 2-year warranty
- ♦ 3-line fusing
- ♦ Discharge resistors per NEC requirements
- ♦ Assembled in the USA

CAPACITOR CELLS

- ♦ 20-year rated life
- ♦ 2-year warranty
- ♦ Self-contained, 3-phase, delta-connected
- ♦ Industrial grade dry-type construction
- ♦ Losses of less than ½ watt per kVAr
- ♦ Self-healing metallized polypropylene dielectric film
- ♦ 3-phase pressure-actuated interrupter
- ♦ Hermetically-sealed tin-plated steel case
- ♦ Threaded insulated terminals

FUSES

- ♦ Fast-acting, current-limiting, with 200,000 ampere interrupting capacity



TRAY DESIGN

- ♦ Dimensions: 8.75 in H x 19.5 in W x 8.5 in D
- ♦ Weight: 13 lb

FIELD WIRING TERMINATION

- ♦ Mechanical connections are provided for all field wiring termination points
- ♦ Refer to product manual for incoming conductor information

OPTIONS

- ♦ Other voltages and frequencies available
- ♦ Other kVAr configurations available