TWNM43012X-3

- Series: Eaton Cutler-Hammer
- 12.5 kVAr, 480 V, 60 Hz, 3-phase
- 15 amps

APPLICATION

- At the load within Motor Control Centers (MCCs)

STANDARD FEATURES

- UL recognized component
- 2-year warranty
- 3-line fusing
- Discharge resistors per NEC requirements
- Assembled in the USA

CAPACITOR CELLS

- 20-year rated life
- 2-year warranty
- Self-contained, 3-phase, delta-connected
- Industrial grade dry-type construction
- Losses of less than ½ watt per kVAr
- Self-healing metallized polypropylene dielectric film
- 3-phase pressure-actuated interrupter
- Hermetically-sealed tin-plated steel case
- Threaded insulated terminals

FUSES

- Fast-acting, current-limiting, with 200,000 ampere interrupting capacity

BLOWN FUSE INDICATION

- Indication light illuminates on outside of enclosure when corresponding fuse has blown

TRAY DESIGN

- Dimensions: 9 in H x 13.75 in W x 7.25 in D
- Weight: 13 lb

FIELD WIRING TERMINATION

- Mechanical connections are provided for all field wiring termination points
- Refer to product manual for incoming conductor information

OPTIONS

- Other voltages and frequencies available
- Other kVAr configurations available