

## TWNM63016-3

- ◆ Series: Eaton Cutler-Hammer
- ◆ 16.7 kVAr, 600 V, 60 Hz, 3-phase
- ◆ 16 amps

## APPLICATION

- ◆ At the load within Motor Control Centers (MCCs)

## STANDARD FEATURES

- ◆ UL recognized component
- ◆ 2-year warranty
- ◆ 3-line fusing
- ◆ Discharge resistors per NEC requirements
- ◆ Assembled in the USA

## CAPACITOR CELLS

- ◆ 20-year rated life
- ◆ 2-year warranty
- ◆ Self-contained, 3-phase, delta-connected
- ◆ Industrial grade dry-type construction
- ◆ Losses of less than ½ watt per kVAr
- ◆ Self-healing metallized polypropylene dielectric film
- ◆ 3-phase pressure-actuated interrupter
- ◆ Hermetically-sealed tin-plated steel case
- ◆ Threaded insulated terminals

## FUSES

- ◆ Fast-acting, current-limiting, with 200,000 ampere interrupting capacity

## BLOWN FUSE INDICATION

- ◆ Indication light illuminates on outside of enclosure when corresponding fuse has blown



## TRAY DESIGN

- ◆ Dimensions: 9 in H x 13.75 in W x 7.25 in D
- ◆ Weight: 16 lb

## FIELD WIRING TERMINATION

- ◆ Mechanical connections are provided for all field wiring termination points
- ◆ Refer to product manual for incoming conductor information

## OPTIONS

- ◆ Other voltages and frequencies available
- ◆ Other kVAr configurations available